

# Silcolapse® 710

## Silicone Antifoam Compound

November 2017

<b>Description</b>	Trial tests should be carried out to determine the quantity of antifoam needed to produce best results and assure no adverse interference with product or process performance. Testing should be started at 10 ppm and increased or decreased based on the results.						
<b>Applications</b>	<p><b>Silcolapse® 710</b> is a broad spectrum antifoaming and defoaming agent which can be used to control or destroy foam in many industrial, food processing and food contact applications. Typical applications in which it can be used include:</p> <ul style="list-style-type: none"> <li>• <b>Beverages, Juices, Sauces and Soup:</b> Many food and beverage applications generate foam, <b>Silcolapse® 710</b> will reduce or eliminate foam problems during the processing of many food and beverage applications</li> <li>• <b>Fruit and Vegetable Washing and Processing:</b> Many fruit and vegetable processes generate foam, <b>Silcolapse® 710</b> will reduce or eliminate foam in raw fruit and vegetable washing, potato processing and sugar beet and sugar cane processing</li> <li>• <b>Dairy Products:</b> Dairy and cheese production and processing can generate foam <b>Silcolapse® 710</b> will reduce or eliminate foam problems during the processing in many dairy production processes</li> <li>• <b>Meat, Poultry and Seafood:</b> Meat, poultry and seafood production and processing can generate foam <b>Silcolapse® 710</b> will reduce or eliminate foam problems in meat and poultry rendering, egg washing and seafood processing and production</li> <li>• <b>Fats and oils:</b> Production and processing materials into edible fats and oils can generate foam <b>Silcolapse® 710</b> will reduce or eliminate foam problems during processing and production</li> <li>• <b>Water / Effluent Treatment:</b> Aerobic and anaerobic water treatment; activated sludge processes, food plant waste water treatment and cooling towers</li> </ul>						
<b>Advantages</b>	<ul style="list-style-type: none"> <li>• Effective in alkaline conditions</li> <li>• Easy to use, either as is or pre-diluted</li> <li>• Cost efficient, effective at low doses</li> <li>• Chemically inert, will generally not alter the properties of the foaming medium</li> <li>• Effective at high temperatures</li> <li>• Kosher certified</li> </ul>						
<b>Characteristics</b>	<table border="1" style="width: 100%;"> <tr> <td style="width: 60%;">• Appearance</td> <td>Grey/white opalescent liquid</td> </tr> <tr> <td>• Actives, %</td> <td>100</td> </tr> <tr> <td>• Diluents</td> <td>Hydrocarbon solvents</td> </tr> </table> <p><small>Please note: The typical properties listed in this bulletin are not intended for use in preparing specifications for any particular application of SILCOLAPSE® silicone materials. Please contact our Technical Service Department for assistance in writing specifications.</small></p>	• Appearance	Grey/white opalescent liquid	• Actives, %	100	• Diluents	Hydrocarbon solvents
• Appearance	Grey/white opalescent liquid						
• Actives, %	100						
• Diluents	Hydrocarbon solvents						
<b>Instructions for use</b>	Trial tests should be carried out to determine the quantity of antifoam needed to produce best results and assure no adverse interference with product or process performance. Testing should be started at 10 ppm and increased or decreased based on the results.						

# Silcolapse® 710

<b>FDA Regulatory Information</b>	<p><b>FDA Status:</b></p> <p>The Ingredients in <b>Silcolapse® 710</b> are permitted for FDA regulated applications as follows:</p> <ul style="list-style-type: none"> <li>• 21 CFR 175.105 Adhesives</li> <li>• 21 CFR 173.340 Defoaming agents</li> <li>• 21 CFR 176.200 Defoaming agents used in coatings</li> <li>• 21 CFR 176.210 Defoaming agents used in the manufacture of paper and paperboard</li> </ul>
<b>EPA Regulatory Information</b>	<p><b>EPA Pesticide Chemical Regulations:</b></p> <p>The Ingredients in <b>Silcolapse® 710</b> are exempt from the requirement of a tolerance under EPA regulations:</p> <ul style="list-style-type: none"> <li>• 40 CFR 180.910</li> </ul>
<b>Packaging</b>	<b>Silcolapse® 710</b> is available in 1000 kg tote containers, 200 kg drums and 20 kg pails.
<b>Storage and Shelf Life</b>	<b>Silcolapse® 710</b> when stored in the original, unopened container between (5-40°C), can be stored for 12 months from the date of manufacture. Beyond this date, Elkem Silicones no longer guarantees that the product meets the sales specifications.
<b>Safety</b>	Please read the product label for <b>Silcolapse® 610</b> and consult the Safety Data Sheet (SDS) before handling to review hazards as well as safe handling and storage information. If you need to obtain the SDS for <b>Silcolapse® 610</b> , please contact your Elkem Silicones representative.

Visit our website [www.silicones.elkem.com](http://www.silicones.elkem.com)

## EUROPE

Elkem Silicones France  
21 Avenue Georges Pompidou  
F69486 Lyon Cedex 03  
FRANCE  
Tel. (33) 4 72 13 19 00  
Fax (33) 4 72 13 19 88

## NORTH AMERICA

Elkem Silicones USA  
2 Tower Center Boulevard  
Suite 1601  
East Brunswick, NJ 08816-1100  
United States  
Tel. (1) 732 227-2060  
Fax. (1) 732 249-7000

## LATIN AMERICA

Elkem Silicones Brazil Ltda.  
Av. Duquesa de Goiás, 716  
2º andar  
05680-002 Sao Paulo  
Brazil  
Tel. (55) 11 4380-6900

## ASIA PACIFIC

Elkem Silicones Hong Kong  
Trading Co. Ltd  
29th Floor, 88 Hing Fat Street  
Causeway Bay  
Hong Kong  
Tel. (852) 3106 8200  
Fax (852) 2979 0241

### Warning to the users

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. ELKEM SILICONES guarantees that its products comply with its sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for given use. Determination of the suitability of product for the uses and applications contemplated by users and others shall be the sole responsibility of users. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and ELKEM SILICONES is at their disposal to supply any additional information.