

# Silcolapse<sup>®</sup> 722

## Silicone Antifoam Emulsion

November 2017

### Description

**Silcolapse<sup>®</sup> 722** is a non-ionic aqueous 20% active silicone antifoam and/or defoamer. It offers excellent antifoam and defoaming properties in a wide variety of aqueous applications including those with incidental food contact as well as food processing applications. The product effectively controls foam at concentrations as low as 10 ppm solids, even at elevated temperatures. The product gives good results at wide-ranging pH and provides a cost-effective solution where foam is a problem.

### Applications

**Silcolapse<sup>®</sup> 722** is a broad spectrum antifoaming and defoaming agent which can be used to control or destroy foam in many industrial, food processing and food contact applications. Typical applications in which it can be used include:

- **Beverages, Juices, Sauces and Soup:** Many food and beverage applications generate foam, **Silcolapse<sup>®</sup> 722** will reduce or eliminate foam problems during the processing of many food and beverage applications
- **Fruit and Vegetable Washing and Processing:** Many fruit and vegetable processes generate foam, **Silcolapse<sup>®</sup> 722** will reduce or eliminate foam in raw fruit and vegetable washing, potato processing and sugar beet and sugar cane processing
- **Dairy Products:** Dairy and cheese production and processing can generate foam **Silcolapse<sup>®</sup> 722** will reduce or eliminate foam problems during the processing in many dairy production processes
- **Meat, Poultry and Seafood:** Meat, poultry and seafood production and processing can generate foam **Silcolapse<sup>®</sup> 722** will reduce or eliminate foam problems in meat and poultry rendering, egg washing and seafood processing and production
- **Fats and oils:** Production and processing materials into edible fats and oils can generate foam **Silcolapse<sup>®</sup> 722** will reduce or eliminate foam problems during processing and production
- **Water/ Effluent Treatment:** Aerobic and anaerobic water treatment; activated sludge processes, food plant waste water treatment and cooling towers

### Advantages

- Easy to use – as supplied or pre-diluted in water or in the medium to be defoamed
- Cost efficient, effective in doses as low as 10 ppm
- Highly effective in most aqueous media, and at many pH levels
- Chemically inert in foaming systems – will not alter the properties of the foaming medium
- Heat resistant – works at application temperatures up to 120°C (248°F)
- Low viscosity allows it to be used with automatic metering systems
- Kosher certified

### Characteristics

• Appearance	Opaque white liquid
• Actives, %	20
• Specific Gravity	~ 1.0
• Viscosity (cPs)	500 - 3000
• Emulsifier Type	Non-ionic
• pH	4 to 6

Please note: The typical properties listed in this bulletin are not intended for use in preparing specifications for any particular application of Silcolapse<sup>®</sup> silicone materials. Please contact our Technical Service Department for assistance in writing specifications.

# Silcolapse® 722

<b>Instructions for use</b>	Trial tests should be carried out to determine the quantity of antifoam needed to produce best results and assure no adverse interference with product or process performance. Testing should be started at 10 ppm and increased or decreased based on the results. For convenience, <b>Silcolapse® 722</b> is designed to be used as is so no dilution is necessary. If needed, a 1% active solution can be made by adding 19 parts water (or foaming solution) to 1 part <b>Silcolapse® 722</b> . Predilution at a level less than 1% is not recommended.
<b>FDA Regulatory Information</b>	<b>FDA Status</b> The Ingredients in <b>Silcolapse® 722</b> are permitted for FDA regulated applications as follows: <ul style="list-style-type: none"> <li>• 21 CFR 175.105 Adhesives</li> <li>• 21 CFR 173.340 Defoaming agents</li> <li>• 21 CFR 176.200 Defoaming agents used in coatings</li> <li>• 21 CFR 176.210 Defoaming agents used in the manufacture of paper and paperboard</li> </ul>
<b>EPA Regulatory Information</b>	<b>EPA Pesticide Chemical Regulations</b> The Ingredients in <b>Silcolapse® 722</b> are exempt from the requirement of a tolerance under  EPA regulations: <ul style="list-style-type: none"> <li>• 40 CFR 180.910</li> </ul>
<b>Packaging</b>	<b>Silcolapse® 722</b> is available in 1000 kg tote containers, 200 kg drums and 20 kg pails.
<b>Storage and shelf life</b>	<b>Silcolapse® 722</b> when stored in the original, unopened container between (5-40°C), can be stored for 9 months from the date of manufacture. Beyond this date, Elkem Silicones no longer guarantees that the product meets the sales specifications.
<b>Safety</b>	Please read the product label for <b>Silcolapse® 722</b> and consult the Safety Data Sheet (SDS) before handling to review hazards as well as safe handling and storage information. If you need to obtain the SDS for <b>Silcolapse® 722</b> , please contact your Elkem Silicones representative.

Visit our website [www.silicones.elkem.com](http://www.silicones.elkem.com)

## EUROPE

Elkem Silicones France  
 21 Avenue Georges Pompidou  
 F69486 Lyon Cedex 03  
 FRANCE  
 Tel. (33) 4 72 13 19 00  
 Fax (33) 4 72 13 19 88

## NORTH AMERICA

Elkem Silicones USA  
 2 Tower Center Boulevard  
 Suite 1601  
 East Brunswick, NJ 08816-1100  
 United States  
 Tel. (1) 732 227-2060  
 Fax. (1) 732 249-7000

## LATIN AMERICA

Elkem Silicones Brazil Ltda.  
 Av. Duquesa de Goiás, 716  
 2º andar  
 05680-002 Sao Paulo  
 Brazil  
 Tel. (55) 11 4380-6900

## ASIA PACIFIC

Elkem Silicones Hong Kong  
 Trading Co. Ltd  
 29th Floor, 88 Hing Fat Street  
 Causeway Bay  
 Hong Kong  
 Tel. (852) 3106 8200  
 Fax (852) 2979 0241

### Warning to the users

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. ELKEM SILICONES guarantees that its products comply with its sales specifications. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for given use. Determination of the suitability of product for the uses and applications contemplated by users and others shall be the sole responsibility of users. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and ELKEM SILICONES is at their disposal to supply any additional information.

# Silcolapse<sup>®</sup> 722